

LAB REFRIGERATOR-FREEZER COMBINATION LD-LRFC-A13



info@labodam.com

www.labodam.com

Lab Refrigerator-Freezer Combination LD-LRFC-A13

Lab Refrigerator-Freezer Combination LD-LRFC-A13 is a refrigerator-freezer combination floor type unit with user-friendly digital control panel, microprocessor controlled system with 310 L net capacity. Refrigerator has +4°C set point and deep freezer has -20°C set point. Audio-visual alarm system for exceeding upper and lower temperature limit, leaving open door and low voltage or electricity cut-off issues.

Features:

- Microprocessor controlled system
- Double thermal gazing door with lock and magnetic seal rings
- Deep freezer door with polyurethane insulated block-door system
- Outer body made up of galvanized sheet, coated with rust proof electrostatic paint
- Adjustable plastic covered wire shelves
- Stainless steel Cr-Ni inner body
- Equal temperature distribution using strengthen fan system
- USB output with 10 years recording memory
- Control panel thermostat with 0.1°C sensitivity
- Easy, user-friendly operation
- Complied with ISO international standards

Applications:

Used in biotechnology, medical, pharmaceutical research laboratories and testing centers to store specimens, biological samples, reagents etc.

Specifications:

Model No.		LD-LRFC-A13	
Total capacity	310 L (230 L refrigerator + 80 L freezer)		
Upper Part (refrigerator)	Temperature range	0 to 15°C	
	Set point	+4 °C	
	Wire shelves	3	
	Net volume	230 L	

	Gross volume	256 L
	Interior lighting	Yes, LED light source
	Door lock	Yes
	Internal dimension (W×L×H)	520 × 560 × 880 mm
Lower Part (freezer)	Freezer section	-10 to -30°C
	Set point	- 20 °C
	Net volume	80 L
	Gross volume	85 L
	Wire shelves	1
	Interior lighting	No
	Door lock	No
	Internal dimension (W×L×H)	470 × 490 × 370 mm
Common features	Rollers for portability	Yes (2 wheels with stopper, 2 regular wheels)
	PC Connection	USB
	External dimension (L×W×H)	650 × 590 × 2000 mm
	Power Supply	220 to 240V, 50/60 Hz
	Gross weight	180 kg

Optional Accessories:

1. Graphic thermal printer